



MY-TE WINCH-HOIST SPECIFICATIONS

DESCRIPTION	STANDARD				MAX	
	100A	10-12	AIR1000	HY1	AC36	DC48
LIFT CAPACITY(LBS) * Double Line-1st Layer	2000	2500	2500	3000	6000	6000
UNIT VOLTAGE	115V/1/60 or 230V/1/60	12 V-DC	Pneumatic **	Hydraulic **	115V/1/60 or 230V/1/60	12 V-DC
DRUM SPEED - FPM No Load	30	10	32	17	11	4
LIFT SPEED-FULL LOAD Single Line	20 FPM @1000 Lb.	9 FPM @1250 Lb.	15 FPM @1250 Lb.	10 FPM @1500 Lb.	7.25 FPM @3000 Lb.	3 FPM @3000 Lb.
FULL LOAD AMPS	19	100			19	100
DUTY CYCLE-PER HOUR Operating at Full Load	25 %	25 %	50 %	50 %	25 %	25 %
CABLE DRUM CAPACITY Normal Cable Size	250 Ft. 1/4"	250 Ft. 1/4"	250 Ft. 1/4"	250 Ft. 1/4"	110 Ft. 3/ 8"	110 Ft. 3/ 8"
UNIT DIMENSIONS W" X H" X L"	12X14X22	12X14X23	12X11X22	9X9X21	13X13X27	13X13X28
SHIPPING WEIGHT - LB.	67	69	77	60	128	138

DESCRIPTION	UTILITY			I-BEAM	VERSATILE	
	300A	30-12	HY3	800 ***	510	520 ****
LIFT CAPACITY(LBS) * Double Line-1st Layer	1600	1600	1600	2000	2000	3000
UNIT VOLTAGE	115V/1/60 or 230V/1/60	12 V-DC	Hydraulic **	115V/1/60 or 230V/1/60	115V/1/60 or 230V/1/60	115V/1/60 or 230V/1/60
DRUM SPEED - FPM No Load	59	21	29	30	12	12
LIFT SPEED-FULL LOAD Single Line	30 FPM @800 Lb.	15 FPM @800 Lb.	29 FPM @800 Lb.	20 FPM @1000 Lb.	12 FPM @1000 Lb.	12 FPM @1500 Lb.
FULL LOAD AMPS	19	100		19	17	17
DUTY CYCLE-PER HOUR Operating at Full Load	25 %	25 %	25 %	25 %	50 %	50 %
CABLE DRUM CAPACITY Normal Cable Size	Rope Capstan	Rope Capstan	Rope Capstan	250 Ft. 1/4"	250 Ft. 1/4"	250 Ft. 1/4"
UNIT DIMENSIONS W" X H" X L"	12X14X18	12X14X18	8X8X16	15X14X25	13X11X32	13X11X32
SHIPPING WEIGHT - LB.	64	65	60	126	115	115

* See Specification Sheet for multiple layer ratings

** See Specification Sheet for supply needed

*** Shipped with 42 Ft. 1/4" Cable and Safety Hook

**** Available in 230V/3/60

Specifications are subject to change without notice.

MY-TE PRODUCTS INC.

9880 E. 30TH ST.
INDIANAPOLIS, IN 46229

PH 317-897-9880 FAX 317-897-9811
E-MAIL MYTE@NETDIRECT.NET